

CHRISTIE HS SERIES D20WU-HS / D20HD-HS

Auditoriums | Enterprise venues and boardrooms | Entertainment venues | Houses of worship
Hotels | Live events and conferences | Rental and staging | Trade shows and exhibitions

High-brightness performance. Light-weight design.

There is no other 1DLP® laser projector with a better lumen-to-weight ratio. Achieving 20,000 lumens and weighing less than 95lbs, the Christie® D20WU-HS and D20HD-HS are the lightest and brightest 1DLP® laser projectors on the market. This powerhouse performance provides a viable alternative to similarly bright 3DLP projectors.

Not only are they bright, they produce amazing, true-to-life visuals thanks to the enhanced color accuracy of Christie's BoldColor™ Technology and HD or WUXGA resolution.

With built-in Christie Twist™, users have the tools needed to quickly and easily set up and align irregular screens and multi-projector displays.

These projectors come with the option to add Christie Mystique® automated camera-based alignment software, letting you quickly stage, install, align, and recalibrate multi-projection systems in minutes.



CHRISTIE®

Technical specifications		Christie D20WU-HS	Christie D20HD-HS
Image	brightness (lumens)	• 20,600 ISO • 18,500 ANSI	• 18,500 ISO • 16,500 ANSI
	color wheel	• 4 segment (RGBY) - 2X or 3X speed	
	contrast (nominal)	• Full on/off (Christie RealBlack™ enabled): 2,000,000:1 • Dynamic contrast: 6000:1 • Full on/off (Christie RealBlack disabled): 1200:1 • ANSI 250:1	
Display technology	type	• 1 x 0.96" DMD	
	native resolution	• 1920 x 1200 (2,304,000 pixels) (16:10)	• 1920 x 1080 (2,073,000 pixels) 16:9
Illumination	type	• Laser phosphor with Christie BoldColor™ Technology	
	performance	• 20,000 hrs to 50% brightness	
Signal Inputs	standard	• HDMI x 2 (HDCP 2.2) (one on side panel, one on bottom) • 3GSDI x 1 (BNC) • DVI-D x 1 (digital only) • VGA x 1 • USB x 1 (Type A) • Wi-Fi® dongle (optional) • HDBaseT (RJ45) x 1	
	signals	• HDTV formats VGA through to WUXGA (1920 x 1200) • Horizontal and vertical scaling while maintaining aspect ratio (all inputs)	
	3D	• HDMI 1.4, HDBaseT - frame packed, top/bottom, side-by-side (up to 120Hz output); frame sequential @ 1080P up to 120Hz. • 3D sync in (BNC) - for genlocking projectors • 3D sync out (BNC) - for genlocking projectors, or controlling emitter or polarizer	
	pixel clock	• 162 MHz	
	scan rates	• Horizontal: 15-91kHz • Vertical: 24-120Hz	
	monitor out (loop-through)	• 3GSDI x 1 (BNC) • HDMI x 1 (HDMI out)	
Control and networking		• HDBaseT (RJ45 x 1) • RJ45 x 1 (Ethernet Control over wired network connection) • RS232 x 1 • Built-in backlit keypad • IR Remote • Remote in: 3.5mm stereo female (provides serial communications and power) • Loop out available for daisy chaining • DC JACK 12VDC, 200 mA.	
Warping and blending	mount type	• Christie Twist™	
	optional	• Christie Twist Premium and Twist Pro • Christie Mystique® automated camera-based alignment	
Lenses	mount type	• Boresight adjustable • Motorized horizontal and vertical lens offset (memory available) • Motorized zoom and focus adjustment (memory available for full ILS lenses)	
	lens options	• 0.38:1 UST lens • 0.84-1.02:1 zoom lens (no zoom/focus memory) • 1.02-1.36:1 zoom lens (no zoom/focus memory) • 1.2-1.5:1 zoom lens (full ILS) • 1.5-2.0:1 zoom lens (full ILS) • 2.0-4.0:1 zoom lens (full ILS) • 4.0-7.0:1 zoom lens (full ILS)	
		• +100/-55% Vertical • +4/-28% Horizontal	• +120%/-65% Vertical • +7%/-15% Horizontal
		• +108/-74% Vertical • +29/-42% Horizontal	
	offsets for 0.38:1 UST lens	• +108/-74% Vertical • +29/-42% Horizontal	
	offsets for 0.84-1.02:1	• +124/-98% Vertical • +40/-49% Horizontal	
	offsets for 1.02:1-1.36:1	• +140% Vertical • ±50% Horizontal	
Accessories	standard	• IR remote with wired remote jack (wire not included) • AC line cord for projector • Product Safety Guide	
	optional	• Christie One Mount Plus (140-117100-XX) • One Mount Extender Rod (121-125109) • One Mount Rigging Kit (used with One Mount, One Mount Plus Extender Rod) (121-126100-XX) • Christie One Rigging Frame (140-113106-XX) • WiFi Dongle (133-113106-XX) • Fog Filter with Frame (003-005714-XX) • Fog Filter module (003-005715-XX)	
Power requirements	operating voltage	• Normal mode: 200-240 VAC @ 50/60Hz with 15A fuse	
	power consumption	• Normal mode: 1710W • Eco1 mode: 1380W • Eco2 mode: 830W	
	operating current	• Normal mode: 9A (200-240 VAC)	
	dissipation	• Normal mode: 5835 BTU/hr • Eco1 mode: 4709 BTU/hr • Eco2 mode: 2832 BTU/hr	
Audible noise		• Standard mode: 44dB(A) • Eco2 mode: 36dB(A) (2x wheel speed) • Standard mode: 45dB(A) • Eco2 mode: 39dB(A) (3x wheel speed)	
Physical	size	• (L xWxH) 26.65 x 23.46 x 7.99" (677 x 596 x 203mm) w/o feet	
	shipping size	• (L xWxH) 37.99 x 31.30 x 14.37" (965 x 795 x 365mm)	
	weight	• 91.52lb (41.6kg)	
	shipping weight	• 117.7lb (53.3kg)	
Operating environment	temperature	• 32-104°F (0-40°C)	
	humidity	• 10-85% non-condensing	
Regulatory		• This product conforms to all relevant European directives, standards, safety, health and environmental concerns • Directives: RoHS • REACH • WEEE • Contact Christie for timing of certifications: UL/CSA/IEC 60950-1 • FCC Class A • cTUVus • CE • FDA • CCC • KC • PSE • EAC • BIS • VCCI • RCM • TER • Mexico • BSMI	
Warranty		• Three years parts and labor on the projector • Three years or 20,000 hours parts and labor on the illumination system ¹ • Contact an authorized Christie representative for full details of our limited warranty	

¹ Reference the Christie Standard Limited Warranty document for details.

For the most current specification information, please visit christiedigital.com

Copyright 2023 Christie Digital Systems USA, Inc. All rights reserved. Our centers of excellence for manufacturing in Kitchener, Ontario, Canada and in Shenzhen, China are ISO 9001:2015 Quality Management System-certified. All brand names and product names are trademarks, registered trademarks or tradenames of their respective holders. "Christie" is a trademark of Christie Digital Systems USA, Inc., registered in the United States of America and certain other countries. DLP® and the DLP logo are registered trademarks of Texas Instruments. Performance specifications are typical. Due to constant research, specifications are subject to change without notice.
CD3925-Christie-HS-Series-D20-Datasheet-Sept-2023-EN

